BLUEPRINTLAB

REACH ALPHA | RA-5002

ALPHA 5 INSPECTOR

A remote multi-sensor measurement tool

Inspect With Ease

The Alpha 5 Inspector is a tough, reliable, intuitive to control manipulator for conducting remote visual and nondestructive inspections.

With high accuracy joint positioning (0.1°) and a master/slave topside controller, the Alpha 5 Inspector is designed to manipulate UT, CP, or other visual/NDT probe heads into position for accurate measurements.



All Electric

Note: Probe head not included

FEATURES

- Fits on very small ROVs and Crawlers
- Quick to integrate
- Probe Holder Available for your Probe Integration, or
- Build-your-own Probe Holder
- Embedded controllers no additional POD
- Self-protection against collision
- One-click stow/deploy position
- Corrosion and scratch resistant anodized aluminium
- Advanced monitor software interface
- Data-logging for probe location



Crawler Proven

ROV and

Master Controller Enabled

- TOUGH 300m Depth Rating **Field Proven**
- USABLE Intuitive Interface Master Arm Controlled
- ADVANCED 0.1° Joint Accuracy **Kinematics and Self-Protection**



Note: Master Arm not included

A Revolution for Subsea Inspection & Intervention





Responsive **Integration Support**



16	2
	4

12 Month Warranty



1000+ Hours Logged




Extended Warranty, **Spares Packages &** Service Plans Available

blueprintlab.com | info@blueprintlab.com | +61 (2) 9519 7651


BLUEPRINTLAB

SPECIFICATIONS

Reach	0.4m & up depending on probe length
Outer Diameter	40mm
Standard Connector	Teledyne 6 Pin IE(W)-55 Impulse Connector (whip included)
End-effector Accuracy	<1cm
Operator Control Options	3D Space Mouse, Gamepad, Software GUI, Master Controller



— High Mobility & Compact



J3 J4 J2 **J1:** 350° **J2:** 155° **J3:** 185° **J4:** 350° J5 **J5:** 200° Note: Custom Probe is an example only • ELECTRICAL Voltage 18-30V Wattage 35W Max


COMS

.J1

ENVIRONMENTAL
Depth 300MSW
Temp -35°C to 35°C
Material AL6061

RS232/485

• MECHANICAL Payload Capacity 2kg Weight (Air) 1360g Weight (Water) 900g



Interface with a variety of industry standard payloads

ACFM



UT + CP Probe

Micro IP Camera